



OZZ XR2 P9"

Experience the power of light with OZZ XR2 P9". These 220 mm lights feature a dynamic start-up position light in white and orange. The innovative successor to the original OZZ light series offers a new prominent start-up pattern for an impressive visual effect upon ignition. With a boost function, the OZZ XR2 P9" emits 10 600 lumen, providing 1 lux at a distance of 680 meters. The driving beam pattern ensures optimal visibility with a wide and long-range reach. The lights have a color temperature of 5000 K, offering pleasant illumination in all conditions.

Art. no.	88102 (white)
Lamp type	LED
Diodes	16 pcs
Voltage	10-35V DC
Actual effect 12V	R112: 74 W, boost: 134 W
Actual effect 24V	R112: 73 W, boost: 130 W
Nominal current at 12 V	10,5 A
Nominal current at 24 V	5,2 A
Theoretical lumen	15000
Actual lumen	R112: 7010, boost: 10600
1 lux @ (m)	R112: 480, boost: 680
Kelvin (K)	5000
IP-class	IP68/IP69K
Beam pattern	driving
Position light	dynamic white & amber
Connection	4-pin DT male+female (1000 mm)
Material chassi, lens	aluminum, polycarbonate
ØxDxH (mm)	220×84,3×210/227
Operating temperature	-40 - +60°C
E-mark approval	R112, R7
EMC	ECE R10
Ref. no.	50
Weight (kg)	2,6
Warranty	3 years

